

DILOG

DC150

Digital cable receiver with embedded Cryptoguard

- 1000 channels
- MPEG-2
- TV-scart
- VCR-scart
- RCA (cvbs out, audio L/R out)
- SPDIF optical
- RS-232
- DVB and teletext
- Embedded Cryptoguard
- Dynamic NIT update
- Teletext (VBI and OSD)
- Software update via OTA
- Aspect ratio : 4:3 full, 4:3 letterbox, 16:9
- 8 x Timer
- 8 x Favourite lists



CryptoGuard

Dilog Nordic AB
Telefon: 031 28 88 30
E-mail: order@dilog.se
Hemsida: www.dilog.se

DILOG

Technical specification

EAN-number	7 350 021 771 506
Frequency range	50-860MHz
Demodulation	QAM 16,32,64,128,256
FEC rate	1/2,2/3,3/4,5/6,7/8
Profile level	MPEG-2 MP@ML
Transport stream	MPEG-2 ISO/IEC 13828-1
Video resolution	720x576 (PAL) 720x480 (NTSC)
Input bit rate (max)	81Mbits/s
Aspect ratio	4:3 , 16:9 , Letterbox
Audio decoding	MPEG / Musicam Layer I & II
Audio mode	20bit dac, Max 2 Vrms, S/PDIF of Dolby digital bitstream out CVBS output, audio L/R output, CVBS input bypass
Conditional Access	Embedded Cryptoguard, Conax optional
Display	Display time and channel number
Audio output	Audio L/R input bypass
TV scart	CVBS/RGB output
RCA	Mono/Left/Right/Stereo
VCR scart	
Input voltage	90-250 (50/60HZ) V/AC
Power supply typ	SMPS
Power consumption	17W
Dimensions	340x60x265 mm
Weight	2.5 kg
Operating temperature	0-50c
Storage temperature	-20-60c



Cryptoguard

Dilog Nordic AB
Telefon: 031 28 88 30
E-mail: order@dilog.se
Hemsida: www.dilog.se